

# FOOTAGE® SPC

WATERPROOF SOLID POLYMER  
CORE FLOORING

<b>CLASSIFICATION</b>	ASTM F-3261-17 Resilient flooring in modular format with Solid Polymeric Core
<b>SIZE</b>	7" x 48" (nom)
<b>OVERALL THICKNESS</b>	4.5 mm (3.5 mm + 1 mm cushion backing)
<b>WEAR LAYER</b>	12 mil featuring enhanced coating
<b>CONSTRUCTION</b>	ABA SPC
<b>EDGE</b>	Bevel
<b>INSTALLATION METHOD</b>	Angle / Angle
<b>WEAR LIMITED WARRANTY</b>	20 Year Residential / 10 Year Light Commercial
<b>PACKAGING</b>	28.84 ft <sup>2</sup> (2.68 m <sup>2</sup> ) per carton 12 pieces per carton 55 cartons per pallet
<b>WEIGHT PER CARTON</b>	42.88 lbs / 19.45 kg



Heavy Shade Variation

**Stardust**  
CAS 3802CB



**Ash Gray**  
CAS 3803CB



**Alabaster**  
CAS 3804CB



Heavy Shade Variation

**Well-Bred**  
CAS 3807CB



Heavy Shade Variation

**Bona Fide**  
CAS 3808CB

## PRODUCT TESTING

<b>Chemical Resistance</b>	ASTM F 925	Passed
<b>Critical Radiant Flux</b>	ASTM E 648	Class I, CRF >1.13
<b>Dimensional Stability</b>	ASTM F 2199	Passed
<b>Residual Indentation</b>	ASTM F 1914	Passed
<b>Resistance to Heat</b>	ASTM F 1514	Passed
<b>Resistance to Light</b>	ASTM F 1515	Passed
<b>Smoke Density</b>	ASTM E 662	Passed
<b>Static Load Limit</b>	ASTM F 970	Passed
<b>Slip Resistance</b>	ASTM C 1028	Passed
<b>IIC Sound Testing</b>	ASTM E 492 ASTM E 989	70
<b>STC Sound Testing</b>	ASTM E 90 ASTM E 413	59

\* All measurements are nominal

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Visit [www.interiorsNA.com](http://www.interiorsNA.com) for full product and warranty details.

Colors also available in glue down LVP  
For more information, please visit [interiorsNA.com](http://interiorsNA.com)



MULTIFAMILY



RESIDENTIAL



LIGHT  
COMMERCIAL



Waterproof | Low Maintenance | Acoustical Attributes | Durable | Hygienic | Kid Friendly | Pet Friendly



INTERIORSNA.COM